

PTS400EX (DP) OE DUAL PURPOSE FRONT OR REAR FLUSH FIT PARKING SENSORS



D-SEN-01947

The Steelmate PTS400EX (DP) OE is a premium 4 sensor front or rear upgradeable parking sensor kit with flush fit sensors and OEM sounding speaker. The system can be programmed to ignore tow bars, nudge bars or spare wheels. The PTS400EX (DP) OE is compatible with our DS1 & DS2 visual displays and can be used as a 2 sensor front or rear system if required. The sensor hole size is 16mm in diameter. The visible external diameter of the sensor head is 16mm and they have detachable cables.

If you wish to install this kit on the front of a vehicle, a set of 2.3m sensor extension cables or 4.5m cables must be purchased.

Main Features

- 58K OE style flush fit sensors for better coverage and excellent stability
- 5-stage audible warning buzzer with adjustable tone pitch and volume
- Option of adding a visual display
- Extendable stopping distance from 30cm to 50cm, ideal for vehicles with tow bars or rear mounted spare wheels and steps
- A simple jumper change when installing allows you to select a front or rear system
- Heavy rain proof design
- All weather design (-40°C>+80°C)
- Anti-false alarm patent
- Easy installation

Technical Parameters

- Voltage: 12/24V
- Temperature: -40>+80°C
- Input: <4W
- Beep volume: 70>90dB
- Range (Rear): 0.3>1.5m
- Range (Front): 0.3>1.0m

Included In The Kit

- 4 x 14D-17 sensor heads with flush fit mounts
- 4 x 2.7m sensor cables
- 1 x ECU
- 1 x Power loom
- 1 x Speaker
- 1 x 4m speaker/visual display extension cable
- 1 x 16mm hole punch
- 1 x User/installation manual